

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
9 June 2005 (09.06.2005)

PCT

(10) International Publication Number  
**WO 2005/053107 A1**


(51) International Patent Classification<sup>7</sup>: **H01R 13/24**  
(21) International Application Number:  
PCT/US2004/039091  
(22) International Filing Date:  
19 November 2004 (19.11.2004)  
(25) Filing Language: English  
(26) Publication Language: English  
(30) Priority Data:  
200320100688.8  
20 November 2003 (20.11.2003) CN

(71) Applicant and  
(72) Inventor: **XU, Xiang** [CN/CN]; Room 601, No.20, Yuesheng Apartment House, Xiaolin Road, Yushan Town, Kunshan City, Jiangsu, China (CN).  
(74) Agent: **WEISS, Stephen, Z.**; Molex Incorporated, 2222 Wellington Court, Lisle, IL 60532 (US).  
(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH,

[Continued on next page]

(54) Title: **SPRING LOADED ELECTRICAL TERMINAL**



(57) Abstract: An electrical terminal (30) includes first (32) and second (34) contact members having outer pressure contacting end portions (32a, 34a) for pressure engaging a pair of electrical devices and enlarged inner end portions (32b, 34b). A sleeve (36) includes a through hole (44) for slidably receiving the inner end portions of the contact members. The through hole has opposite open ends (46, 48) through which the pressure contacting end portions of the contact members project for engaging the spaced electrical devices. A biasing member (38) is disposed in the through hole to resiliently bias the contact members in opposite directions. The biasing member is in a relaxed condition when the pressure contacting end portions of the contact members are out of pressure engagement with the electrical devices. Thereby, one of the contact members can be retracted substantially into the through hole to thereby reduce the distance between distal ends of the pressure contacting end portions of the contact members.

WO 2005/053107 A1



GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

— *with amended claims*

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

— *with international search report*